

Zadzwoń, pomożemy wybrać: +48 511 065 456

FAS

Sprężarki śrubowe firstAir ze stałą prędkością obrotową silnika. Seria FAS dostępna w wersji 10 bar (g).

Machine Model			3	4	6	7	11	15	18	22	30	37	45	55	75	90	
Cooling Type			Air-cooled														
Transmission method			Belt driven										Direct drive				
FAD	8 bar (g)	m ³ /min	0,36	0,52	0,76	1,15	1,74	2,11	2,98	3,62	5,20	5,94	7,60	9,60	13,00	15,20	
	10 bar (g)	m ³ /min	0,32	0,47	0,70	1,05	1,52	1,98	2,67	3,25	4,57	5,10	6,90	8,80	11,70	13,60	
Power		kW - Hp	3	4	5,5	7,5	11	15	18,5	22	30	37	45	55	75	90	
Noise level		dBA	65 ± 3			68 ± 3			70 ± 3			72 ± 3		75 ± 3			
Starting method		Type	Star/Delta starting														
Voltage/Frequency		V/Hz	380/400/415V, 50Hz										380/400/415V, 50Hz				
Protection Level		Class	IP55														
Insulation Class		Type	F														
Drive Motor Efficiency		Type	IE 3														
Discharge temperature		°C	Ambient temperature +15														
Air Outlet			G1/2	G1/2	G1/2	G3/4	G3/4	G3/4	G1 1/4	G1 1/4	G1 1/2	G1 1/2	G2	G2	G2	G2	
Configuration parameters	Standard type FAS	Length	mm	660	660	660	800	880	880	1050	1050	1000	1000	1400	2250	2250	2250
		Width	mm	600	600	600	800	830	830	880	880	1250	1250	1100	1344	1344	1344
		Height	mm	890	890	890	995	1075	1075	1260	1260	1310	1310	1600	1694	1694	1694
		Weight	kg	220	230	240	280	300	400	500	570	850	880	1080	2150	2250	2450
		Connection outlet		G1/2	G1/2	G1/2	G3/4	G3/4	G3/4	G1 1/4	G1 1/4	G1 1/2	G1 1/2	G2	G2	G2	G2
	Air receiver model FAS-R	Tank capacity	lt	200	200	200	270	500	270	500	270	500					
		Length	mm	1500	1500	1500	1400	2000	1450	2000	1450	2000					
		Width	mm	700	700	700	900	900	900	900	900	900					
		Height	mm	1550	1550	1550	1800	1800	1900	1900	1900	1900					
		Weight	kg	335	345	355	460	505	480	525	580	625					
		Connection outlet		G1/2	G1/2	G1/2	G3/4	G3/4	G3/4	G3/4	G3/4	G3/4					
	Air receiver + dryer model FAS-AT	Tank capacity	lt	200	200	200	270	500	270	500	270	500					
		Length	mm	1500	1500	1500	1500	2000	1500	2000	1500	2000					
		Width	mm	700	700	700	900	900	900	900	900	900					
		Height	mm	1550	1550	1550	1800	1800	1900	1900	1900	1900					
		Weight	kg	425	435	445	560	605	580	625	680	725					
		Connection outlet		G1/2	G1/2	G1/2	G3/4	G3/4	G3/4	G3/4	G3/4	G3/4					

Dane i parametry zostały zarejestrowane zgodnie z normą ISO Annex C 1217 - Poziom dźwięku został zmierzony zgodnie z normą PNEUROP / CAGI.